

5.1 - Linear Program

We interpret G with each edge

Unknown macro: 'mathinline'

 colored by read mappings as a flow network, considering the read volume assigned to every (super-) edge as a flux created by the expression of the underlying supporting transcripts T . Consequently, given an edge

Unknown macro: 'mathinline'

 the contribution of the supporting transcripts

Unknown macro: 'mathinline'

 to the flux

Unknown macro: 'mathinline'

 observed along e can be described by a linear equation

Unknown macro: 'mathinline'

(Equation 1)

where f_i represents a factor that expresses the fraction of the respective transcript expression t_i observed between $tail_e$ and $head_e$. In the trivial case, f_i corresponds to the proportion of the interval $[tail_e; head_e]$ in comparison to the entire length of the processed transcript. The correction factor

Unknown macro: 'mathinline'

 in Eq.1 is to compensate for divergence from the expectation created by stochastic sampling intrinsic to RNA-Seq experiments.

The crux of the flux is that an RNA-Seq experiment provides a series of observations on the underlying expression level t_i along the transcript body. Following tradition in transportation problems, we model all of these observations as a system of linear equations by inferring Equation 1 on all

Unknown macro: 'mathinline'

. Subsequently, the linear equations spanned by a locus are resolved by the objective function

Unknown macro: 'mathinline'

(Equation 2)

Solving the linear program (Eq.2) imposed by a locus intrinsically provides an estimate for the expression level t_i of all alternative transcripts that are annotated.